



Iwaki Sanwa Nomenclature Guide

MP SERIES

MP

210	-	1
-----	---	---

N

20

A

N

1 2 3 4 5 6

1 Pump size	210 = 1" x 3/4" 220 = 1" x 3/4" 221 = 1" x 3/4" 222 = 1" x 3/4" 420 = 1-1/2" x 1" 421 = 1-1/2" x 1" 541 = 2" x 1-1/2" 542 = 2" x 1-1/2"	4220 = 1-1/2" x 1" 4220LF = 1-1/2" x 1" 5225LF = 2" x 1" 5430 = 2" x 1-1/2" 8415 = 3" x 1-1/2" 8420 = 3" x 1-1/2" 8515 = 3" x 2"
2 Impeller Code	1: Standard Default	
3 Motor Connection	N: Nema I: IEC	
4 Horse Power	10 = 1 HP 20 = 2 HP 30 = 3 HP 50 = 5 HP 75 = 7.5 HP X0 = 10 HP X5 = 15 HP Y0 = 20 HP	
5 Connection	A = ASME 150# Flange J = JIS Flange	
6 Temperature	N = Standard Temperature pump: -4°F to 248°F (-20°C to 120°C) H = High Temperature Pump: 249°F to 302°F (121 to 150°C) L = Low Temperature Pump: -22°F to -5°F (-30°C to -21°C)	

MMP SERIES

MMP

11	-	1
----	---	---

N

05

N

N

1 2 3 4 5 6

- | | | |
|----------|-------------------------|---|
| 1 | Pump size | 11 = 1/2" x 1/2"
21 = 3/4" x 3/4"
22 = 1" x 3/4" |
| 2 | Impeller Code | 1: Standard Default |
| 3 | Motor Connection | N: Nema
I: IEC |
| 4 | Horse Power | 03 = 1/3 HP
05 = 1/2 HP
07 = 3/4 HP |
| 5 | Connection | N = NPT |
| 6 | Temperature | N = Standard Temperature pump: -4°F to 248°F (-20°C to 120°C)
H = High Temperature Pump: 249°F to 302°F (121 to 150°C)
L = Low Temperature Pump: -22°F to -5°F (-30°C to -21°C) |